Bitumen Hormoz Pars



Zeolite Specification

Description:

Natural Zeolite (Clinoptilolite grade) is a crystalline, hydrated aluminosilicate of alkali and alkaline earth metals. It features high cation exchange capacity (CEC ≥120 meq/100g), strong adsorption properties, and a porous crystalline structure that enables excellent ion exchange and molecular sieving performance.

The product is supplied as a light gray to cream powder or granule and is used across agricultural, environmental, and industrial applications.

Applications:

- Agriculture & Soil Amendment (ammonium adsorption, pH buffering)
- Livestock & Poultry (odor control, litter treatment)
- Odor & Gas Control (NH3, VOC adsorption)
- Construction & Oilfield (lightweight aggregate, drilling fluid additive)

Packing:

- Palletized bag in container
- 1 m³ jumbo bags in container

Health and Safety:

- Zeolite is **chemically inert and non-toxic** under normal handling conditions.
- Avoid generating or inhaling dust; prolonged exposure to airborne particles may cause mild respiratory irritation.
- Use adequate ventilation and personal protective equipment (PPE) such as masks, gloves, and safety glasses when handling fine powders.
- Store in a cool, dry, and well-ventilated area, away from moisture, acids, and incompatible materials.
- Dispose of waste material in accordance with local environmental regulation

Zeolite Analysis

Component	Unit	Typical Range
SiO ₂	%	68.95
Al ₂ O ₃	%	11.14
Fe ₂ O ₃	%	0.97
CaO	%	4.83
MgO	%	0.79
Na ₂ O	%	0.95
K ₂ O	%	0.95
SO ₃	%	0.068

Tel: +98 21 72065436 Web: www.bhpbitumen.com Email: Info@bhpbitumen.com

Add: No.11, Golkhane St, Nelson Mandella Blvd, Tehran, Iran

Bitumen Hormoz Pars



Unit	Typical Range	
%	10.64	
Physical Properties		
Unit	Typical Value	
_	Fine powder, cream to light gray	
%	≤1.0	
g/cm³	0.85 - 0.95	
_	7.5 – 9.0	
	% ysical Propertion Unit — %	

Zeolite Raw & Powder

Applications





Email: Info@bhpbitumen.com